

Horizon

CRB-160

A cover creaser that communicates with BQ-160 binder!

Even heavy-weight cover stock can be used to build crisp, clean and tight books.



BQ-160

CRB-160


Features

- Impact scoring position is set automatically according to the book thickness inserted into the BQ-160.
- Clean and sharp impact creases can be made even with heavier and laminated stock.
- Stand alone model is also available with an integrated touch screen operation console.
- A wide variety of impact scoring patterns can be selected from the touch screen.
- Suitable for crease covers, restaurant menus, greeting cards and all digital print applications.

Eliminate the problem of image cracking of heavier covers and digital printed sheets.

Operation console

The CRB Creasers can be set-up through the BQ-160 color touch screen. Cover creasing and a variety of other creasing patterns can be selected from the touch screen.



Impact creasing section

Impact creasing position is automatically set according to the book thickness inserted into the BQ-160. Depth of the creasing can also be set depending on cover thickness.



CRB-160

CRS-36 (Stand alone model)

A stand alone model is available with built in touch screen. Suitable for impact creasing restaurant menus, greeting cards and various types of heavier stock.



CRS-36

Delivery tray

Creased sheets are delivered at a comfortable height for easy handling.



CRB-160 / CRS-36 Major Specifications

Sheet Size	Max. 364(W) x 650(L) mm (14.33" x 25.59") Min. 140(W) x 180(L) mm (5.52" x 7.09")
Pre-set Size	A3 / A4 / A5 / B4 / B5, 8.5x11" / 8.5x14" / 11x17" / 12x18"
Sheet weight Range	Normal Paper, Coated Paper 81.4 to 407 gsm
Impact Scoring Mechanism	1 Set Each (Convex and Concave)
Maximum Scoring Line	Eight Scoring Lines
Production speed	Length 430 mm (16.9"), Four Scoring Lines, 4 sec/sheet
Voltage/Frequency	Single Phase 115 V, 50 / 60 Hz, Single Phase 230 V, 50 / 60 Hz
Power Consumption (Including pump)	Single Phase 115 V, 50 Hz : 76 W, Single Phase 115 V, 60 Hz : 74 W Single Phase 230 V, 50 Hz : 79 W, Single Phase 230 V, 60 Hz : 71 W
Machine dimensions	CRB-160 : 1,326(W) x 610(D) x 980(H) mm (52.3" x 24.1" x 38.6") CRS-36 : 1,326(W) x 630(D) x 1,272(H) mm (52.2" x 24.8" x 50.1")
Installation Space	2,326(W) x 1,610(D) mm (91.6" x 63.4")
Machine Weight	CRB-160 : 82 kg (180.8 lb) CRS-36 : 85 kg (187.4 lb)

*The machine design and specifications are subject to change without any notice.

Distributed by

HORIZON INTERNATIONAL, INC.

510 Kuze Ooyabu-cho, Minami-ku, Kyoto, 601-8206, Japan Phone : +81-(0)75-934-6700, Fax : +81-(0)75-934+6708, www.horizon.co.jp